

State of Ohio Environmental Protection Agency

## **Southwest District Office**

OG E-0298

401 East Fifth Street Dayton, Ohio 45402-2911 TELE: (937) 285-6357 FAX: (937) 285-6404

6446.3F

December 24, 2003

Mr. William J. Taylor U.S. Department of Energy, Fernald Area Office P.O. Box 538705 Cincinnati, OH 45253-8705

RE: CONCURRENCE TO USE GCL THAT DOESN'T REQUIRE LOOSE BENTONITE

Dear Mr. Taylor:

This letter provides Ohio Environmental Protection Agency concurrence with the use of a new geosynthetic clay liner product which does not require the use of loose granular bentonite to seal the overlaps between adjacent panels. The new gcl is Bentomat SuperGrove, a trademarked product manufactured by CETCO. We agree that this product complies with the original design which specified that the use of loose or powdered bentonite to seal seams should be performed in accordance with the manufacturer's recommendations.

The OSDF Construction Quality Assurance Plan should be changed to accommodate use of the new product. A provision should be added to inspect the gcl for the presence of the groove either continuously as it is deployed or by spot checking at several intervals along the panel length.

Should you have any questions, please contact Tom Ontko or me.

Sincerely,

Thomas A. Schneider Fernald Project Manager

Office of Federal Facilities Oversight

cc:

Jim Saric, U.S. EPA

Terry Hagen, Fluor Fernald Mark Shupe. GeoTrans. Inc.

Michelle Cullerton, Tetra Tech EM Inc.

Ruth Vandergrift, ODH

Q:\ou2\gclsupergroove.wpd